

SPEC SHEET

LOCATED IN Pensacola, FL

PRICE \$295,000

CONTACT Mark Egan

EMAIL megan@lonemtn.com

PHONE +1-612-321-6489



Check out this Avidyne equipped SR22 G3 Turbo. Stay comfortable with factory air conditioning and have the added performance of the Tornado Alley Turbo System. Some additional upgrades include, Dual Garmin GTN 650s, digital fuel gauges, and digital backup attitude indicator. Complete logbooks available upon request.

Competitive financing rates available so contact Lone Mountain Aircraft today to learn more about how to get this great aircraft into your hangar soon!

Embark training available for owner pilots who qualify.



SPEC SHEET

FAST FACTS

Garmin GTN 650s Avidyne G3 Turbo Air Conditioning CiES Digital Fuel Gauges

AIRFRAME, ENGINE, & PROP

Airframe:

1825 Flight Hours since new Annual completed April 2025 Useful Load of 935 Pounds CAPS Overhaul Due November 2026

Engine:

2125 Engine Hours since new Continental IO-550, 310hp Tornado Alley Turbo Normalizing System

Prop:

1825 Hours since new Hartzell 3-Blade Composite Propeller

AVIONICS

Avidyne Entegra Primary Color Flight
Display (PFD)
Avidyne EX 5000 Multifunction Display
Garmin GMA 340 Audio Panel /
Intercom
Dual Garmin GTN 650s
Avidyne DFC90 Digital Autopilot
Flight Director
Avidyne TAS 600 Traffice Advisory
System
XM Datalink Weather and Audio
CMAX Electronic Approach Charts
EMAX Electronic Engine Monitoring
Garmin GTX345 ADS-B out Transponder
406 Mhz ELT

ADDITIONAL FEATURES

Factory air conditioning
TKS Weeping Wing De-Icing System
CiES Digital Fuel Gauges
Rear Tinted Windows
Whelen LED Wingtip Lights
Polished Spinner
Leather Wrapped Side-Yoke, Throttle
Lever and Grab Handles



SPEC SHEET

SAFETY FEATURES

Cirrus Airframe Parachute System (CAPS) Airbag Seatbelts Roll Cage RC Allen 2610-3 Backup Digital Attitude Indicator

EXTERIOR & INTERIOR

Exterior:

Premium White paint with black and silver stripes

Interior:

Black perforated leather interior with black and gray accents and a gray headliner ALL SPECIFICATIONS SUBJECT TO VERIFICATION UPON INSPECTION



SPEC SHEET







